

ACTFLEX SUPERPRIME 008

TECHNICAL DATA SHEET

Non-pigmented, solvent-based primer

DESCRIPTION

ACTFLEX SUPERPRIME 008 is a solvent-based primer, appearing colorless to slightly yellow, which forms a thin layer upon interaction with moisture. This layer serves as a crucial bonding agent between substrates and adhesives. Specifically engineered to optimize adhesion before applying 1-component MS sealants or water-based products.

AREAS OF APPLICATION:

ACTFLEX SUPERPRIME 008 is utilized to enhance adhesion on various plastics and wood surfaces including GRP, epoxy resins, PVC, ABS, concrete, stone fiber reinforced floor slab, magnesium floor slab, and glass magnesium floor slab to improve PU sealants between adhesive and substrates. Preliminary tests on original substrates under production conditions are essential due to the diverse nature of plastics. Seek manufacturer's advice and conduct tests before using on materials prone to stress cracking. Suitable for professional users only; perform tests to ensure adhesion and material compatibility. Excellent permeability to porous substrates and sealing effect. It serves as a special primer for MS sealants and water-based waterproofing products such as ACTFLEX 906 WPU.

ACTFLEX SUPERPRIME 008 PROPERTIES

Colour	Clear	Application Method	Brush, Felt Or Foam Applicator
Tack Free Time (23°C)	3 To 5 MIN	Chemical Base	Solvent-Based Polyurethane Solution.
Solid Content % JC/T 408	30	Size	1000mL
Density G/Cm3 GB/T 13 447.2)	0.9, Approx.	Application Temperature	5~35

METHOD OF APPLICATION:

Ensure surfaces are clean, dry, and free from contaminants. Adhesion may be improved by additional pre-treatment processes such as scuffing, cleaning, and activation before primer application. Apply a thin, covering coat using a brush, felt, or foam applicator. Ideal application temperature is between 15 °C and 25 °C. ACTFLEX SUPERPRIME 008 should be applied once only, ensuring adequate coverage. Consumption and application method depend on substrate specifics. Seal container tightly after each use.

IMPORTANT NOTE:

ACTFLEX SUPERPRIME 008 is a moisture-reactive system. Reseal the container immediately after use to maintain product quality. Dispose of the product one month after frequent use or after two months of infrequent use. Discard the primer immediately if gelling, separation, or a significant increase in viscosity occurs. Do not dilute or mix with other substances. Adequate UV protection is mandatory when used on transparent or translucent substrates.

CLEANING

Clean up immediately while still wet. Wipe down with solvent to clean tools & equipment. Once dry, is difficult to remove and mechanical means may be necessary. No.1. Observe all OH&S and MSDS information pertaining to safe usage and handling of solvents.

DO NOT discharge product or water from cleaning into sewer or waterways.
DO NOT touch the spill material.

STORAGE

12ON months in the original unopened containers stored in cool, dry conditions 10-22°C. Protect the material against moisture and direct sunlight. Storage above this temperature may reduce storage life. Uncured product is combustible so keep all sources of ignition away from product and its vapours and DO NOT store in pits, depressions, basements or areas where vapours may be trapped. ACTFLEX SUPERPRIME 008 is sensitive to airborne moisture. It is preferable to use all contents of the container after opening.

SAFETY - WHEN HANDLING DO NOT EAT, DRINK OR SMOKE.

ACTFLEX SUPERPRIME 008 is hazardous and may cause skin and/or eye irritations. Always use in a well-ventilated area and wear PPE gloves, safety boots and protective eyewear (against splashes). Use breathing respirators at all times. Organic vapour respirators with particulate pre-filters and powered, air-purifying respirators are NOT suitable. Change soiled work clothes and wash hands before breaks and after finishing work. In case of eye contact, rinse with plenty of water: If inhaled, remove to fresh air, if discomfort persists, if any breathing difficulties occur or if swallowed (do NOT induce vomiting), immediately contact the Poisons Information centre and seek medical attention. KEEP OUT OF REACH OF CHILDREN. Uncured product is combustible so keep all sources of ignition away from product and its vapours. In emergency, contact any Poisons Information Centre (phone 13 11 26 within Australia) or 0800 764 766 (NZ). or a doctor for advice. IN TRANSPORT EMERGENCY DIAL 000 – POLICE-FIRE BRIGADE. Local regulations as well as health and safety advice on packaging labels must be observed.

For more information, please download a copy of the SDS from www.thewaterproofingshop.com.au

Data Sheet

This Technical Data Sheet and the Material Safety Data Sheet (SDS) may be revised at any time to comply with relevant changes to the Australian Standards or to include changes to current technology. Always read the current SDS and TDS carefully prior to use as application and performance data may change from time to time. It is always best to request a copy of the latest technical data from Actech Protective Coatings by calling 02 8021 3517 or emailing admin@actechpc.com.au.

Data provided is typical but does not constitute a full specification. This should be sighted from the company for specific projects.

CONDITIONS OF USE, PRODUCT DISCLAIMER AND STATEMENT OF RESPONSIBILITY

The information supplied is given in good faith and to the best of our knowledge is true and accurate at the time of printing. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use of application and no warranty as to accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. We reserve the right to update information without prior notice to you to reflect our ongoing research and development program. The customer or the contractor is responsible for checking the suitability of products for their intended use. It is the customers' responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standards. Our instructions and recommendations are only for intended users only. Any advice, recommendation, information, assistance or service provided by Actech Protective Coatings in relation to its products or their use is given in good faith, however is provided without responsibility or liability. To the full extent permitted by law, Actech Protective Coatings Products liability is limited to its discretion, to replace or to refund the purchase price of the quantity of the products supplied. Actech Protective Coatings does not exclude rights and remedies that cannot be excluded by legislation, for example under the Consumer Guarantees Act 1993. Under no circumstances will the company be liable for loss, consequential or otherwise, arising from the use of the product.



ACTECH PROTECTIVE COATINGS

(02) 8021 3517 admin@actechpc.com.au Unit 22/872 Canterbury Road Roselands NSW 2196
www.thewaterproofingshop.com.au